

High Current Common Mode Choke

Features

- Surface mountable (multiple case sizes), high current common mode choke for DC power line
- Base terminals are treated, allows for easy mounting on PCB
- Paired wire coil for high stability
- Optimized for transmission of high quality signals
- Operating temperature: -40 °C to +125 °C
- Rated Current: Based on temp. rise; T: 40 °C, typical
- Material categorization: For definitions of compliance please see



Applications



- LAN's, telephones, personal computers
- CD-ROM drives, electronic games
- Other electronic devices

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	COMMON MODE IMPEDANCE AT 100 MHz (Ω)	RATED VOLTAGE MAX. (V _{DC})	RATED CURRENT MAX. (mA)	DC RESISTANCE MAX. (Ω)	INSULATION RESISTANCE MIN. (M Ω)
CMF2L701WIT	700	80	8000	0.006	10
CMF2L102WIT	1000	80	6000	0.014	10


High Current Common Mode Choke

PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY




High Current Common Mode Choke


Dimensions in mm



PART NUMBER	A	B	C	D	E	F	G
CMF2L Series	12.0 ± 0.5	11.0 ± 0.5	6.4 ± 0.3	2.7 ± 0.2	2.5 ± 0.2	7.0 ± 0.2	2.5 ± 0.2




Dimensions in mm



PART NUMBER	H	I	J	K
CMF2L Series	14.0	7.0	2.7	5.2

High Current Common Mode Choke

RECOMMENDED REFLOW PROFILE



Preheating			Soldering		Peak	
Temp.	Time		Temp.	Time	Temp.	Time
T1	T2	t1	T3	t2	T4	t3
150°C	180°C	60 to 120s	230°C	25 to 35s	250°C	5s


RELIABILITY TEST METHOD

ELECTRIC

NO.	Test items	Standard	Experiment Method
1	Temperature characteristics	$\Delta L / L \text{ } 20^{\circ}\text{C} \leq \pm 10\%$	The test should be done after the sample has stabilized in the ring The temperature of the product is -40 to +125 °C, and the L (ΔL) value of the product is the same as the original L value. Suitable for normal temperature and humidity should be $\Delta L / L \text{ } 20^{\circ}\text{C} \leq \pm 10\%$.
2	Load test	The product must not have any damage, such as smoke or sparks	1.2 times the rated current, the time is 5 minutes

High Current Common Mode Choke

ENVIRONMENTAL CHARACTERISTICS

NO.	Test items	Standard	Experiment Method								
1	Reflow soldering	Do not have any damage or problems	Reflow of temperature distribution Before the heat: 150-180 °C, Times 60 to 120sec Peak temperature: 250 ± 5 °C, Times 5 sec Hold temperature: 230 ± 5 °C, Times 30 ± 5 sec 								
2	Solderability	Welding area of more than 90%	The solder surface is immersed in flux and then immersed in a furnace at 235 ± 5 °C for 5 seconds								
3	Low temperature storage	$\Delta L / L_0 \leq \pm 10\%$, there should be no mechanical damage	The sample should be left for 96 ± 4 hours at a temperature of -40 ± 3 °C and returned to the normal temperature range of 1 hour after completion of the test.) 90-95%.								
4	High temperature storage	$\Delta L / L_0 \leq \pm 10\%$, there should be no mechanical damage	The sample should be left for 96 ± 4 hours at a temperature of 125 ± 3 °C. The test should be carried out after returning to normal temperature range for 1 hour.								
5	Constant hot and humid	$\Delta L / L_0 \leq \pm 10\%$, there should be no mechanical damage.	Samples should be left for 96 ± 4 hours at 60 ± 2 °C and 90 °C to 90% humidity (RH). The test is resumed after 1 hour in the normal temperature range.								
6	Temperature cycle	1, no visible mechanical damage. 2, the value of change is less than 10%. 3, the resistance value of less than 5%	In the -25 °C to +85 °C between the respective keep 15min, transit time ≤1min, the number of cycles 5 times, recovery time: 24h test finished (recovery time at least 4h)								
7	vibration	$\Delta L / L_0 \leq \pm 10\%$ There should be no mechanical damage	The sample should be soldered to the printed circuit board When the vibration has an amplitude and 1.5 mm Frequency from 10-55Hz / 1 minute, repeated should be applied to three directions (X, Y, Z) for 2 hours, a total of 6 hours								
8	Impact resistance (MIL-STD-202G Method 213B)	Change in inductance: within ± 10% DC resistance change: ± 10% within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. Then, follow the following test conditions. <table><tr><th>Pulse</th><th>Half sine shock</th></tr><tr><td>Acceleration</td><td>980 m/s²(100g)</td></tr><tr><td>Nominal pulse duration</td><td>6 ms</td></tr><tr><td>Speed change</td><td>3.75 m/s</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Pulse	Half sine shock	Acceleration	980 m/s ² (100g)	Nominal pulse duration	6 ms	Speed change	3.75 m/s
Pulse	Half sine shock										
Acceleration	980 m/s ² (100g)										
Nominal pulse duration	6 ms										
Speed change	3.75 m/s										

High Current Common Mode Choke




9	Thermal shock (MIL-STD-202G Method 107G)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. Test sample according to the specified time Are placed at a specific temperature, as shown in the table below, from step 1 to step 4. <table><tr><th colspan="3">1 cycle condition</th></tr><tr><th>Step</th><th>Temperature ($^{\circ}\text{C}$)</th><th>Time (minute)</th></tr><tr><td>1</td><td>-55 ± 3</td><td>30 ± 3</td></tr><tr><td>2</td><td>Room temperature</td><td>3 or less</td></tr><tr><td>3</td><td>-125 ± 3</td><td>30 ± 3</td></tr><tr><td>4</td><td>Room temperature</td><td>3 or less</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	1 cycle condition			Step	Temperature ($^{\circ}\text{C}$)	Time (minute)	1	-55 ± 3	30 ± 3	2	Room temperature	3 or less	3	-125 ± 3	30 ± 3	4	Room temperature	3 or less
1 cycle condition																					
Step	Temperature ($^{\circ}\text{C}$)	Time (minute)																			
1	-55 ± 3	30 ± 3																			
2	Room temperature	3 or less																			
3	-125 ± 3	30 ± 3																			
4	Room temperature	3 or less																			
10	Wet heat resistance (MIL-STD-202G Method 106G)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. Test samples must be placed in a constant temperature and humidity box, according to the table specified temperature and humidity, do not pass the current test. <table><tr><td>Temperature</td><td>$65\pm 2^{\circ}\text{C}$</td></tr><tr><td>Humidity</td><td>$90\%\pm 10\%\text{RH}$</td></tr><tr><td>Time</td><td>500 ± 24 hours</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$65\pm 2^{\circ}\text{C}$	Humidity	$90\%\pm 10\%\text{RH}$	Time	500 ± 24 hours												
Temperature	$65\pm 2^{\circ}\text{C}$																				
Humidity	$90\%\pm 10\%\text{RH}$																				
Time	500 ± 24 hours																				
11	Low temperature life (IEC68-2-1Ad)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. The test sample should then be placed in the test conditions as shown in the table below. <table><tr><td>Temperature</td><td>$-40\pm 3^{\circ}\text{C}$</td></tr><tr><td>Time</td><td>500 ± 24 hours</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$-40\pm 3^{\circ}\text{C}$	Time	500 ± 24 hours														
Temperature	$-40\pm 3^{\circ}\text{C}$																				
Time	500 ± 24 hours																				
12	Low temperature load life (IEC68-2-1Ad)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. The <table><tr><td>Temperature</td><td>$-55\pm 2^{\circ}\text{C}$</td></tr><tr><td>Plus load current</td><td>Rated current</td></tr><tr><td>Time</td><td>500 ± 24 hours</td></tr><tr><td>Hourly power time</td><td>3/4 power 1/4 power off</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$-55\pm 2^{\circ}\text{C}$	Plus load current	Rated current	Time	500 ± 24 hours	Hourly power time	3/4 power 1/4 power off										
Temperature	$-55\pm 2^{\circ}\text{C}$																				
Plus load current	Rated current																				
Time	500 ± 24 hours																				
Hourly power time	3/4 power 1/4 power off																				
13	Damp heat load (MIL-STD-202G Method 108A)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. Test samples shall be placed in a constant temperature and humidity box, according to the table specified in the temperature and humidity under the continuous access to the rated current for testing. <table><tr><td>Temperature</td><td>$60\pm 2^{\circ}\text{C}$</td></tr><tr><td>Humidity</td><td>$90\sim 95\%\text{RH}$</td></tr><tr><td>Time</td><td>500 ± 24 hours</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$60\pm 2^{\circ}\text{C}$	Humidity	$90\sim 95\%\text{RH}$	Time	500 ± 24 hours												
Temperature	$60\pm 2^{\circ}\text{C}$																				
Humidity	$90\sim 95\%\text{RH}$																				
Time	500 ± 24 hours																				

High Current Common Mode Choke

14	High temperature life test (IEC68-2-2Ba)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. The test sample shall be placed in a constant temperature and humidity tank and the current shall not be supplied at the temperature specified in the table. <table><tr><td>Temperature</td><td>$125\pm 3^{\circ}\text{C}$</td></tr><tr><td>Time</td><td>500 ± 24 hours</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$125\pm 3^{\circ}\text{C}$	Time	500 ± 24 hours				
Temperature	$125\pm 3^{\circ}\text{C}$										
Time	500 ± 24 hours										
15	High temperature load life test (MIL-STD-202G Method 108A)	Change in inductance: within $\pm 10\%$ DC resistance change: $\pm 10\%$ within the appearance of no obvious abnormalities, should not have mechanical damage.	The test sample shall be soldered to the test substrate by reflow soldering. The <table><tr><td>Temperature</td><td>$85\pm 2^{\circ}\text{C}$</td></tr><tr><td>Plus load current</td><td>Rated current</td></tr><tr><td>Time</td><td>2000 ± 24 hours</td></tr><tr><td>Hourly power time</td><td>3/4 power 1/4 power off</td></tr></table> Recovery: 2 hours of recovery in standard condition and subsequent testing within 48 hours.	Temperature	$85\pm 2^{\circ}\text{C}$	Plus load current	Rated current	Time	2000 ± 24 hours	Hourly power time	3/4 power 1/4 power off
Temperature	$85\pm 2^{\circ}\text{C}$										
Plus load current	Rated current										
Time	2000 ± 24 hours										
Hourly power time	3/4 power 1/4 power off										

High Current Common Mode Choke

Dimensions in mm



Order information

Model	shipping
CMF2L701WIT	500/Tape&Reel
CMF2L102WIT	500/Tape&Reel