
1.0Amp Super Fast Recovery Surface Mounted Rectifiers

Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Idea for printed circuit board
- Glass passivated junction chip
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed 260℃/10 seconds at terminals

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Mechanical Data

Case : Molded plastic body
Terminals : Solder plated, solderable per MIL-STD-750,Method 2026
Polarity : Polarity symbol marking on body
Mounting Position : Any
Weight : 0.0014 ounce, 0.038 grams

Marking



Product Name,X : A.B.....J

Maximum Ratings And Electrical Characteristics

Ratings at 25℃ ambient temperature unless otherwise specified. Single phase half-wave 60Hz,resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Symbols	E1AF	E1BF	E1CF	E1DF	E1FF	E1GF	E1JF	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	150	200	300	400	600	V
Maximum RMS voltage	V_{RMS}	35	70	105	140	210	280	420	V
Maximum DC blocking voltage	V_{DC}	50	100	150	200	300	400	600	V
Maximum average forward rectified current at T_L=100℃	$I_{(AV)}$	1.0							A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	30.0							A
Maximum instantaneous forward voltage at 1.0A	V_F	1.0				1.3		1.7	V
Maximum DC reverse current T_A =25℃ at rated DC blocking voltage T_A=125℃	I_R	2.0 200							uA
Maxinum reverse recovery time(Note 1)	Trr	35							ns
Typical junction capacitance (Note2)	C_J	18.0							pF
Typical thermal resistance	R_{qJA}	70.0							°C/W
Operating junction and storage temperature range	T_J,T_{STG}	-55 to +150							℃

Note: 1.Reverse recovery time test condition: IF=0.5A IR=1.0A Irr=0.25A
2.Measured at 1MHz and applied reverse voltage of 4.0V D.C.

1.0Amp Super Fast Recovery Surface Mounted Rectifiers

Ratings And Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PERLEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS






FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS




1.0Amp Super Fast Recovery Surface Mounted Rectifiers

Dimensions in inches and (millimeters)

SMAF




Suggested Pad Layout



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.90	0.154
D	2.00	0.078
E	5.10	0.200

1.0Amp Super Fast Recovery Surface Mounted Rectifiers

Suggested Soldering Temperature Profile




Note

- Recommended reflow methods: IR, vapor phase oven, hot air oven, wave solder.
- The device can be exposed to a maximum temperature of 260°C for 10 seconds.
- Devices can be cleaned using standard industry methods and solvents.
- If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.

Package Information

Carrier Dimension(mm)



A0	B0	K0	D0	E	F
2.83	4.75	1.42	1.55	1.75	5.50
P0	**P1**	**P2**	**T**	**W**	**Tolerance**
4.0	4.0	2.0	0.25	12	0.1

Package Specifications

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (Kpcs)	Box Size (mm)	QTY/Box (Kpcs)	Carton Size (mm)	Q'TY/Carton (Kpcs)
SMAF	7'	178	3	180	12	380*200*200	120
	11'	278	7.5	285	15	355*310*310	120