1-Line, Bi-directional, Transient Voltage Suppressors


Descriptions

The ESD12D070TA is a bi-directional TVS (Transient Voltage Suppressor). It is specifically designed to protect sensitive electronic components that may be subjected to ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lightning. It is particularly well-suited for cellular phones, portable device, digital cameras, power supplies and many other portable applications because of its small package and low weight.

The ESD12D070TA may be used to provide ESD protection up to ±20KV Air, ±20KV contact compliance to IEC61000 -4-2 , and withstand peak pulse current up to 8 A (8/20μs) according to IEC61000-4-5.



DFN1006-2L



Circuit diagram

Features

- Stand-off voltage: ± 12V Max
- Transient protection for each line according to
  IEC61000-4-2 (ESD): ±20KV Air, ±20KV contact
  IEC61000-4-4(EFT): 40 A (5/50 ns)
  IEC61000-4-5 (Surge): 8 A (8/20**μ**s)
- Solid-state silicon technology

Order information

Device	Marking	Package	Shipping
ESD12D070TA	S	DFN1006	10000/Tape&Reel

Applications

- Cell phone handsets and accessories
- Personal Digital Assistants (PDAs)
- Notebooks, Desktops, and Serves
- Portable Instrumentation
- Digital Cameras
- CAR/MID DVD/MP3/MP4/PMP Players

Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Peak pulse current (t_p = 8/20μs)	I_{PP}	8.0	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±20	kV
ESD according to IEC61000-4-2 contact discharge		±20	
Operation junction temperature	T_J	-50~125	°C
Lead temperature	T_L	260	°C
Storage temperature	T_{STG}	-65~150	°C

Electrical characteristics (TA=25 °C ,unless otherwise noted)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V_{RWM}				±12.0	V
Reverse leakage current	I_R	V_{RWM} = 12V			0.2	uA
Reveres breakdown voltage	V_{BR12}	I_T=1mA	13.0			V
Clamping voltage	V_C	Ipp=1A tp=8/20us			16.0	V
		Ipp=8 A tp=8/20us			20.0	V
Junction capacitance	C_J	V_R = 0V, f = 1MHz		10.0		pF


Electrical performance curve

V_C: Maximum clamping voltage

V_{br}: Reverse breakdown voltage


V_{RWM}: Working voltage

I_{PP}: Maximum peak current




Bi–Directional TVS


Typical characteristics (T_A=25°C, unless otherwise noted)




8/20μs waveform per IEC61000-4-5




Contact discharge current waveform per IEC61000-4-2




Clamping voltage vs. Peak pulse current




Capacitance vs. Reveres voltage




Non-repetitive peak pulse power vs. Pulse time



Power derating vs. Ambient temperature



ESD clamping
(+8kV contact discharge per IEC61000-4-2)




ESD clamping
(-8kV contact discharge per IEC61000-4-2)

Package outline dimensions

DFN1006-2L

DIMENSION OUTLINE: Unit:mm



Recommened Mounting Pad Layout Unit:mm

