

1-Line, Unidirectional Transient Voltage Suppressors


Descriptions

The ESD5B005TR is a Unidirectional TVS (Transient Voltage Suppressor). It is specifically designed to protect sensitive electronic components that may be subjected to ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lightning. It is particularly well-suited for cellular phones, portable device, digital cameras, power supplies and many other portable applications because of its small package and low weight.

The ESD5B005TR may be used to provide ESD protection up to $\pm 20\text{kV}$ air discharge $\pm 15\text{kV}$ contact discharge according to IEC61000-4-2, and withstand peak pulse current up to 4.0A (8/20 μs) according to IEC61000-4-5.



SOD-523



Circuit diagram

Features

- Stand-off voltage: 5V Max
- Transient protection for each line according to
IEC61000-4-2 (ESD): $\pm 20\text{kV}$ air discharge $\pm 15\text{kV}$ contact discharge
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5 (surge): 4.0A (8/20 μs)
- Solid-state silicon technology
- Low leakage current

Applications

- Cell phone handsets and accessories
- Personal Digital Assistants (PDAs)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Digital Cameras
- MID/CAR DVD/MP3/MP4/PMP Players

Order information

Device	Marking	Package	Shipping
ESD5B005TR	5L	SOD-523	3000/Tape&Reel

Absolute maximum ratings


Parameter	Symbol	Rating	Unit
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	4.0	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 20	kV
ESD according to IEC61000-4-2 contact discharge		± 15	
Operation junction temperature	T_J	-55~150	$^{\circ}C$
Lead temperature	T_L	260	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

Electrical characteristics (TA=25 $^{\circ}C$,unless otherwise noted)







Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V_{RWM}				5.0	V
Reverse leakage current	I_R	$V_{RWM} = 5.0V$			0.2	μA
Forward voltage	V_{BR21}	$I_F = 1mA$	5.5	6.8	9.0	V
Clamping voltage	V_C	$I_{pp} = 1A$ $t_p = 8/20\mu s$		9.5		
		$I_{pp} = 4.0A$ $t_p = 8/20\mu s$			14.0	V
Junction capacitance	C_J	$V_R = 0V$, $f = 1MHz$		0.5	0.7	pF

Electrical performance curve

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
I_F	Forward Current
V_F	Forward Voltage @ I_F




Typical characteristics ($T_A=25^\circ\text{C}$, unless otherwise noted)




Package outline dimensions

SOD-523



Symbol	Dimensions in millimeter		
	Min.	Typ.	Max.
A	0.510	0.640	0.770
A1	0.500	0.600	0.700
b	0.250	0.300	0.350
c	0.080	0.115	0.150
D	0.750	0.800	0.850
E	1.100	1.200	1.300
E1	1.500	1.600	1.700
E2	0.200 Ref		
L	0.010	0.040	0.070
θ	7° Ref		

Recommend land pattern (Unit: mm)



Note: This land pattern is for your reference only. Actual pad layouts may vary depending on application.