

1-Line, Bi-directional, Transient Voltage Suppressors


Descriptions

The ESD5D015TA is a bi-directional TVS (Transient Voltage Suppressor). It is specifically designed to protect sensitive electronic components that may be subjected to ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lightning. It is particularly well-suited for cellular phones, portable device, digital cameras, power supplies and many other portable applications because of its small package and low weight.

The ESD5D015TA is available in DFN1006-2L package. Standard products are Pb-free and Halogen-free.



DFN1006-2L



Circuit diagram

Features

- Stand-off voltage: $\pm 5.0\text{V}$ Max
- Transient protection for each line according to IEC61000-4-2 (ESD): $\pm 30\text{KV}$ Air, $\pm 30\text{KV}$ contact
IEC61000-4-5 (Surge): 15A ($8/20\mu\text{s}$)
- Solid-state silicon technology
- Low leakage current

Order information

Device	Marking	Package	Shipping
ESD5D015TA	5S	SOD-882	10000/Tape&Reel

Applications

- Cell phone handsets and accessories
- Personal Digital Assistants (PDAs)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Digital Cameras
- CAR/MID DVD/MP3/MP4/PMP Players

Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	15.0	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	
Operating temperature	T_{OP}	-40~125	$^{\circ}C$
Lead temperature	T_L	260	C
Storage temperature	T_{STG}	-55~150	$^{\circ}C$

Electrical characteristics (TA=25 $^{\circ}C$, unless otherwise noted)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V_{RWM}				± 5.0	V
Reverse leakage current	I_R	$V_{RWM} = 5.0V$			0.2	μA
Reverse breakdown voltage	V_{BR}	$I_T = 1mA$	5.5	8.0		V
Clamping voltage	V_C	$I_{PP} = 1A$ $t_p = 8/20\mu s$		9.0		V
		$I_{PP} = 15A$ $t_p = 8/20\mu s$		11.0	12.0	V
Junction capacitance	C_J	$V_R = 0V$, $f = 1MHz$		1.5	2.0	pF


Electrical performance curve

V_C : Maximum clamping voltage







V_{br} : Reverse breakdown voltage

V_{RWM} : Working voltage



I_{PP} : Maximum peak current




Typical characteristics ($T_A=25^\circ\text{C}$, unless otherwise noted)



ESD clamping test setup and waveforms




ESD clamping
(+8kV contact discharge per IEC61000-4-2)



ESD clamping
(-8kV contact discharge per IEC61000-4-2)

Package outline dimensions

DFN1006-2L



Recommended Mounting Pad Layout Unit:mm

