

- ISO 7637-2^(a):
 - Pulse 1: $V_S = -100\text{ V}$
 - Pulse 2a: $V_S = +50\text{ V}$
 - Pulse 3a: $V_S = -150\text{ V}$
 - Pulse 3b: $V_S = +100\text{ V}$

Description

The SMCJ15CA has been designed to protect automotive sensitive circuits against surges defined in ISO 7637-2 and against electrostatic discharges according to ISO 10605.

The Planar technology makes it compatible with high-end circuits where low leakage current and high junction temperature are required to provide reliability and stability over time. The SMCJ15CA devices are packaged in SMC (SMC footprint in accordance with IPC 7531 standard).



Bidirectional

SMC
(JEDEC DO-214AB)

Features

- Peak pulse power:
 - 1500 W (10/1000 μs)
- Stand off voltage range: 15V
- Unidirectional and bidirectional types
- Operating $T_{j\text{ max}}$: 150 °C
- High power capability at $T_{j\text{ max}}$:
 - 1500 W (10/1000 μs)
- registered package outline
- Resin meets UL 94, V0

Complies with the following standards

- ISO 10605 - C = 150 pF, R = 330 Ω :
 - 30 kV (air discharge)
 - 30 kV (contact discharge)
- ISO 10605 - C = 330 pF, R = 330 Ω
 - 30 kV (air discharge)
 - 30 kV (contact discharge)

1 Characteristics

Table 1. Absolute maximum ratings ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameter		Value	Unit
V_{PP}	Peak pulse voltage	ISO10605 (C = 330 pF, R = 330 Ω)		
		contact discharge	30	
		air discharge	30	
		IEC 61000-4-2 /ISO10605 (C = 150 pF, R = 330 Ω)		
		contact discharge	30	
		air discharge	30	kV
P_{PP}	Peak pulse power dissipation ⁽¹⁾	$T_{j \text{ initial}} = T_{amb}$	1500	W
T_{stg}	Storage temperature range		-65 to + 150	$^{\circ}\text{C}$
T_j	Operating junction temperature range		-55 to + 150	$^{\circ}\text{C}$
T_L	Maximum lead temperature for soldering during 10 s.		260	$^{\circ}\text{C}$

1. For a surge greater than the maximum values, the diode will fail in short-circuit.

Figure 1. Electrical characteristics - definitions




Figure 2. Pulse definition for electrical characteristics




Table 2 Electrical characteristics parameter values ($T_b = 25\text{ }^{\circ}\text{C}$)

Part Number	Marking	Reverse Stand-off Voltage	Breakdown Voltage Min.@ I_T	Breakdown Voltage Max.@ I_T	Test Current	Maximum Clamping Voltage @ I_{PP}	Peak Pulse Current	Reverse Leakage @ V_{RWM}
		V_{RWM} (V)	V_{BR} (V)	V_{BR} (V)	I_T (mA)	V_C (V)	I_{PP} (A)	I_R (μ A)
SMCJ15CA	SMCJ15CA	15.0	16.70	18.50	1	24.4	61.5	1





Figure 3. Peak pulse power dissipation versus initial junction temperature (typical value)

Figure 4. Peak pulse power versus exponential pulse duration (T_j initial = $25\text{ }^{\circ}\text{C}$)

Figure 5. Clamping voltage versus peak pulse current (exponential waveform, maximum values)

Figure 6. Junction capacitance versus reverse applied voltage for unidirectional types (typical values)


Figure 7. Junction capacitance versus reverse applied voltage for bidirectional types (typical values)




Figure 8. Leakage current versus junction temperature (typical values)




Figure 9. Peak forward voltage drop versus peak forward current (typical values)




Figure 10. Relative variation of thermal impedance, junction to ambient, versus pulse duration





Figure 11. Thermal resistance junction to ambient versus copper surface under each lead



2 Package information

- Case: DO-214AB molded plastic over planar junction
- Terminals: solder plated, solderable as per MIL-STD-750, Method 2026
- Polarity: for unidirectional types the band indicates cathode
- Flammability: epoxy is rated UL 94, V0
- RoHS package

Figure 16. IPAK dimension definitions




Table 3. SMC dimension values

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	2.90	3.20	0.114	0.126
c	0.15	0.40	0.006	0.016
D	5.55	6.25	0.218	0.246
E	7.75	8.15	0.305	0.321
E1	6.60	7.15	0.260	0.281
E2	4.40	4.70	0.173	0.185
L	0.75	1.60	0.030	0.062

Figure 17. SMC footprint dimensions in mm (inches)

