Description



The femtoSMDC series provides surface mount overcurrent protection for applications where space is at a premium and resettable protection is desired.

Features

- RoHS compliant, lead-free and halogen free
- Fast response to fault currents
- Compact design saves board space
- Low resistance，Low-profile
- Compatible with high temperature solders

Applications

- USB peripherals，Disk drives，CD-ROMs
- Plug and play protection for motherboards and peripherals
- PDAs / digital cameras
- Game console port protection
- Tablet and Notebook PCs
- E-readers

SMD1206 Series Performance Specification


Model	Marking	V_{max} (V dc)	I_{max} (A)	I_{hold} @25°C (A)	I_{trip} @25°C (A)	Maximum Time To Trip Current (A)	Maximum Time To Trip Time (Sec)	Resistance $R_{i\,min}$ (Ω)	Resistance $R1_{max}$ (Ω)
SMD1206R200SF-2	JK	6.0	100	2.00	3.50	8.00	1.00	0.018	0.080

Thermal Derading Chart

Recommended Hold Current(A) at Ambient Temperature(°C)


Model	Ambient Operation Temperature								
	-40°C	-20°C	0°C	25°C	40°C	50°C	60°C	70°C	85°C
SMD1206R200SF-2	2.60	2.44	2.35	2.00	1.78	1.67	1.50	1.45	1.10

Physical Dimensions(mm.)



Model	A		B		C		D	E
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Min.
SMD1206R200SF-2	3.00	3.60	1.50	1.90	0.70	1.70	0.15	0.10


Recommended Pad Layout (mm.)



Packaging Quantity

Part Number	Quantity
SMD1206R200SF	3500 pcs/reel

Soldering Parameters



Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate(Ts max to T p)	3℃/second mac.
Preheat -Temperature Min(Ts min) -Temperature Max(Ts max) -Time(Ts min to Ts max)	 150℃ 200℃ 60~180 seconds
Time maintained above: -Temperature(TL) -Time(tL)	 217℃ 60~150 seconds
Peak Temperature(Tp)	260℃
Ramp-Down Rate	6℃/second max.
Time 25℃ to Peak Temperature	8 minutes max
Storage Condition	0℃~35℃,30%~60%RH

Recommended reflow methods: IR, vapor phase oven, hot air oven, N2 environment for lead-free

Recommended maximum paste thickness is 0.25mm

Devices can be cleaned using standard industry methods and solvents.

Note 1:All temperature refer to topside of the package, measured on the package body surface.

Note 2: If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.